














	Cylinder	Grip Texture	Mfr. I.D/ Item #	Press
	<b>Delivery Finger</b> WxL: 12.6 x 54.2mm Between Holes Ctr-Ctr: 22.3mm	D/C	<b>10404F</b> 20/3020-D	SBB, SBG, SBD, S-Line
	<b>Delivery Finger</b> WxL: 12.6 x 54.2mm Between Holes Ctr-Ctr: 22.3mm	U/C	<b>1404F</b> 20/3020-U	SBB, SBG SBD, S-Line
	<b>Feed Board</b> WxL: 9.5 x 49.8mm Between Holes Ctr-Ctr: 12mm	D/C U/C	<b>34-020-035F</b> 20/3021-D 20/3021-U	GTO, KSB, KS, KSBA 46-52"
	<b>Feed Board</b> WxL: 9.5 x 49.8mm Between Holes Ctr-Ctr: 12mm	D/C U/C	20/3022-D 20/3022-U	KSB, KS, KSBA, Letterpress
	<b>Delivery Finger</b> WxL: 12.6 x 54.4mm Between Holes Ctr-Ctr: 22.3mm	D/C U/C	20/3023-D 20/3023-U	KORD, GTO 52"
	<b>Rack Finger</b> WxL: 12.6 x 76mm Between Holes Ctr-Ctr: 19mm	D/C U/C	<b>1451</b> 20/3024-D 20/3024-U	S-LINE, SDB
	<b>Rack Finger Cover Plate</b> WxL: 12.6 x 60mm Between Holes Ctr-Ctr: 19mm	D/C U/C	<b>Cover plate for 20/3024</b> 20/3029 20/3029	S-LINE, SDB
	<b>Feed Finger</b> WxL: 9 x 45.3mm Between Holes Ctr-Ctr: 7.8mm	D/C U/C	<b>03-020-035</b> 20/3026-D 20/3026-U	S-LINE, SB, SBG, SBD
<b>Delivery Bar</b>				
	<b>Delivery Bar</b> Repair gripper bar. Machine old pad surface oil and screw on a new diamond coated steel pad surface. Reconditioned only.	D/C	20/3027	KORD
	<b>Diamond Covers</b> To improve the gripping texture of each pad. Set of 35	D/C	20/3034	
<b>Side Guide Bars</b>				
	<b>Side Guide Bar</b> 12.371" long	D/C	20/3030	Speedmaster
	<b>Side Guide Bar</b> 14.2" long	D/C	20/3031	
<b>Plate Clamp</b>				
	<b>Strips</b> Length: 200mm/7.875" Length: 134mm/5.275" Length: 80mm/3.150"	D/C D/C D/C	20/3032-1 20/3032-2 20/3032-3	<i>Diamond coated spring steel strips that can be bonded to the clamping bar to give a new clamping surface</i>